

## **Expanded Level Switch Product Offerings**

SOR® is pleased to introduce two new products to our extensive line of point level devices – the 2210 chambered level switch and the redesigned 1710 direct mounted level switch – both are engineered to reduce costs and increase flexibility.

The new 2210 chambered level switch is designed with maximum flexibility in mind. Standard temperature ratings of 800 degrees F and pressure ratings of 1500 psi mean that a single product can be used in almost every application. The 2210 also introduces a few new features such as our "Quick Release" cover for applications that only require Ordinary Location approvals. The 2210 has actually been used for years in targeted markets with great success and is now available worldwide.

In addition to the 2210, we are announcing a redesign of our popular 1710 direct mounted level switch. This redesign not only increases our standard pressure and temperature ratings for flexibility, but also adds IEC and North American Hazardous Location approvals in one device.

While the 1710 and the 2210 share a common core design, they do have some differences that make each one uniquely suited for certain applications.





1710

2210

## **APPLICATIONS**

Standard Direct Mount 2" NPT (Chamber Available)

Standard Chamber Included (Direct Mount Not Available)

## **APPROVALS**

Explosion Proof - CSA (US & Canada) Flameproof - ATEX/IECEx

Ordinary Locations - CSA (US & Canada)

## HOUSING

Aluminum NEMA 4X IP66
Full Explosion Proof Threaded Cover

Aluminum NEMA 4X IP66
"Quick Release" Threaded Cover

Learn more about these products and the <u>entire line of level</u> <u>switches</u> at sorinc.com or call (913) 888-2630 to speak to an SOR customer service representative.

SORING.COM

MEASUREMENT AND CONTROL

**Engineered to Order with Off-the-Shelf Speed**